



SAFETY DATA SHEET

ProChemOnline.com



SECTION 1 PRODUCT AND COMPANY INFORMATION

PRODUCT NAME: **Platinum Sponge**

PRODUCT NUMBER: 2869

CAS NUMBER: 7440-06-4

MANUFACTURER:

Prochem, Inc.
826 Roosevelt Road
Rockford, IL 61109

PHONE: 815-398-1788
FAX: 815-398-1810
TOLL FREE: 800-795-8788

IN CASE OF TRANSPORTATION EMERGENCY CONTACT CHEM-TREC: 1-800-424-9300

SECTION 2 HAZARDS IDENTIFICATION

CLASSIFICATION OF SUBSTANCE OR MIXTURE

Pictogram



Signal Word

Danger

Hazard Statements

H228 Flammable solid.

Precautionary Phrases

P210	Keep away from heat/sparks/open flames/hot surfaces. –No smoking.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting/equipment.
P280	Wear protective gloves/eye protection/face protection.
P370+P378	In case of fire: Use dry sand, dry chemical, or alcohol-resistant foam for extinction.

HMIS CLASSIFICATION:

Health: 1 Chronic: * Fire: 2 Reactivity Hazard: 1

NFPA RATING:

Health: 1 Flammability: 2 Reactivity Hazard: 1

EYE CONTACT: May cause slight to mild irritation of the eyes.

SKIN CONTACT: May cause slight to mild irritation of the skin.

INHALATION: May be irritating to the nasal cavity and respiratory tract.

INGESTION: No specific information is available on the physiological effects of ingestion.

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Formula: Pt

Molecular Weight: 195.08

CHEMICAL NAME	CAS#	%
Platinum Sponge	7440-06-4	100

SECTION 4 FIRST AID MEASURES

EYE EXPOSURE: Immediately flush the eyes with copious amounts of water for at least 15 minutes. Assure flushing under eyelids. A victim may need assistance in keeping their eyelids open. Get immediate competent medical attention.

SKIN EXPOSURE: Wash affected area with plenty of water. Remove contaminated clothes if necessary. Seek medical assistance if irritation persists.

INHALATION: Remove to fresh air and keep at rest. Closely monitor the victim for signs of respiratory problems, such as difficulty in breathing, coughing, wheezing, or pain. In such cases, seek immediate medical assistance.

INGESTION: Seek medical assistance immediately. Keep the victim calm. Give the victim water (only if conscious). Induce vomiting only if directed by medical personnel.

SECTION 5 FIREFIGHTING MEASURES

FLASH POINT: Not available

AUTO IGNITION TEMPERATURE: Not available

EXPLOSION LIMITS: Not available

EXTINGUISHING MEDIUM: Use dry sand, dry chemical, or alcohol-resistant foam for extinction.

SPECIAL FIRE FIGHTING PROCEDURES: Wear self-contained, approved breathing apparatus and full protective clothing, including eye protection and boots.

HAZARDOUS COMBUSTION AND DECOMPOSITION PRODUCTS: Platinum oxide

SECTION 6 ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS: Wear all appropriate equipment when using this material. Ensure adequate ventilation. Avoid dust formation. Avoid breathing dust.

ENVIRONMENTAL PRECAUTIONS: Prevent spillage from entering drains or allowing to be released into the environment.

METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP: Sweep up and place in suitable container for proper disposal.

SECTION 7 HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING: Wear appropriate personal protective equipment. Ensure adequate ventilation. Avoid contact with skin and eyes. Keep away from sources of ignition.

CONDITIONS FOR SAFE STORAGE: Store in cool, dry, and well-ventilated area. Do not store with oxidizing agents and acidic materials.

SECTION 8 EXPOSURE CONTROLS AND PERSONAL PROTECTION

EXPOSURE CONTROLS:

Component	Exposure Limits	Basis	Entity
Platinum	1.0000 mg/m ³	TLV	ACGIH
	0.002 mg/m ³	PEL	OSHA

TLV: Threshold Limit Value over 8 hours of work.

PEL: Permissible Exposure Limit

EYE PROTECTION: Wear chemical safety glasses or goggles and face shield.

SKIN PROTECTION: Wear nitrile or rubber gloves, and a complete suit protecting against chemicals.

VENTILATION: Provide local exhaust, preferably mechanical.

RESPIRATOR: Use an approved respirator.

ADDITIONAL PROTECTION: Provide eyewash stations, quick-drench showers and washing facilities accessible to areas of use and handling.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

COLOR AND FORM: White to silver solid

ODOR: None

MOLECULAR WEIGHT: 195.08

BOILING POINT: 3827° C

MELTING POINT: 1772° C

SPECIFIC GRAVITY: 21.45 gm/ml

VAPOR DENSITY: No data available

SOLUBILITY: Insoluble

SECTION 10 STABILITY AND REACTIVITY

STABILITY: Stable

HAZARDOUS POLYMERIZATION: Will not occur

CONDITIONS TO AVOID: Heat, flames, and sparks.

INCOMPATIBILITY: Strong oxidizing agents and alcohols

DECOMPOSITION PRODUCTS: Platinum oxide

SECTION 11 TOXICOLOGICAL DATA

ACUTE TOXICITY: Not available

CARCINOGENIC EFFECTS: No component of this product present at levels greater than or equal to 0.1% is considered to be a human carcinogen.

MUTAGENIC EFFECTS: Not available

TETRAOGENIC EFFECTS: Not available

CHRONIC TOXICITY: Not available

RTECS: TP2160000

To the best of our knowledge the toxicological effects of this compound have not been fully investigated.

SECTION 12 ECOLOGICAL DATA

No information available

SECTION 13 DISPOSAL CONSIDERATIONS

Dispose of in according to local, state, and federal regulations.

SECTION 14 TRANSPORTATION DATA

DOT: UN3089

Metal powders, flammable, n.o.s.

(Platinum)

CLASS 4.1

PG III

IATA: UN3089

Metal powder, flammable, n.o.s.

(Platinum)

CLASS 4.1

PG III

Marine Pollutant: No

SECTION 15 REGULATORY INFORMATION

SARA 302/304: Not Listed

SARA 311/312: Fire Hazard, Chronic Health Hazard

SECTION 15 REGULATORY INFORMATION (Cont.)

SARA (TITLE 313): Not listed

CALIFORNIA PROP. 65: Not Listed

MASSACHUSETTS RIGHT TO KNOW COMPONENTS: Platinum

NEW JERSEY RIGHT TO KNOW COMPONENTS: Platinum.

PENNSYLVANIA RIGHT TO KNOW COMPONENTS: Platinum

SECTION 16 OTHER INFORMATION

DISCLAIMER: The information herein is believed to be accurate and reliable as of the date compiled. However, Prochem, Inc. makes no representation, warranty, or guarantee of any kind with respect to the information in this document or any use of the product based on the information.

DATE PREPARED: 04/15

SDS DEPT.