



SAFETY DATA SHEET

ProChemOnline.com



SECTION 1 PRODUCT AND COMPANY INFORMATION

PRODUCT NAME: **Nickel (II) Sulfate Hydrate**
PRODUCT NUMBER: 2713-5
CAS NUMBER: 15244-37-8
SYNONYMS: Nickelous sulfate hydrate, sulfuric acid, nickel(2+)salt
MANUFACTURER:

ProChem, Inc.
826 Roosevelt Road
Rockford, IL 61109

PHONE: 815-398-1788
TOLL FREE: 800-795-8788

IN CASE OF TRANSPORTATION EMERGENCY CONTACT CHEM-TREC: 1-800-424-9300

SECTION 2 HAZARDS IDENTIFICATION

CLASSIFICATION OF SUBSTANCE OR MIXTURE

Pictogram



Signal Word

Danger

Hazard Statements

H302+H332	Harmful if swallowed or if inhaled.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H341	Suspected of causing genetic defects.
H350i	May cause cancer by inhalation.
H360	May damage fertility or the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure if inhaled.
H410	Very toxic to aquatic life with long lasting effects.

Precautionary Phrases

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P260	Do not breathe dust/fume/gas/mist/vapors/spray.
P264+P265	Wash face and hands thoroughly after handling. Do not touch eyes.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing should not be allowed out of the workplace.
P280	Wear protective gloves/protective clothing/eye protection/respasatory protection/face protection
P301+P312	IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.
P302+P352	IF ON SKIN: Wash with plenty of soap and water.
P304+P340+P342+P316	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms: Get emergency medical help immediately.

SECTION 2 HAZARDS IDENTIFICATION (Cont.)

HMIS CLASSIFICATION:

Health: 2 Chronic: * Fire: 0 Reactivity Hazard: 1

NFPA RATING:

Health: 2 Flammability: 0 Reactivity Hazard: 1

EYE CONTACT: May cause severe irritation to the eyes.

SKIN CONTACT: May cause slight to mild irritation of the skin. May cause sensitization by skin contact. Prolonged contact may lead to dermatitis.

INHALATION: May be irritating to the nose, mucous membranes, and respiratory tract.

INGESTION: Ingestion may lead to dizziness, abdominal cramps, vomiting, bloody diarrhea, weakness, and convulsions.

CHRONIC HEALTH EFFECTS: Long term exposure to nickel and nickel compounds may lead to skin irritation and dermatitis. May cause cancer and heritable genetic damage. May cause allergy or asthma symptoms or breathing may become difficult if inhaled.

ACUTE HEALTH EFFECTS: Harmful if swallowed. May be irritating to skin, eyes, and respiratory tract, causing intestinal disorders, convulsions, asphyxia, sensitization dermatitis, allergic asthma, and pneumonitis.

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Formula: $\text{NiSO}_4 \cdot \text{XH}_2\text{O}$

Molecular Weight: 154.76 (anhy.)

CHEMICAL NAME	CAS#	%
Nickel (II) Sulfate Hydrate	15244-37-8	100

SECTION 4 FIRST AID MEASURES

EYE EXPOSURE: Immediately flush the eyes with copious amounts of water for at least 15 minutes. Assure flushing under eyelids. A victim may need assistance in keeping their eyelids open. Get immediate competent medical attention.

SKIN EXPOSURE: Wash affected area with soap and plenty of water. Remove contaminated clothes if necessary. Seek medical assistance if irritation persists.

INHALATION: Remove to fresh air and keep at rest. Closely monitor the victim for signs of respiratory problems, such as difficulty in breathing, coughing, wheezing, or pain. In such cases, seek immediate medical assistance.

INGESTION: Seek medical assistance immediately. Keep the victim calm. Give the victim water (only if conscious). Induce vomiting only if directed by medical personnel.

SECTION 5 FIREFIGHTING MEASURES

FLASH POINT: Product is not flammable

AUTO IGNITION TEMPERATURE: Not available

EXPLOSION LIMITS: Not available

EXTINGUISHING MEDIUM: Use fire fighting measures that suit the surrounding fire.

SPECIAL FIRE FIGHTING PROCEDURES: Wear self-contained, approved breathing apparatus and full protective clothing, including eye protection and boots.

HAZARDOUS COMBUSTION AND DECOMPOSITION PRODUCTS: Sulfur oxides and nickel oxides

SECTION 6 ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS: Wear all appropriate equipment when using this material. Ensure adequate ventilation. Avoid dust formation. Avoid breathing dust.

ENVIRONMENTAL PRECAUTIONS: Prevent spillage from entering drains or allowing to be released into the environment.

METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP: Spills can be mixed with powdered sodium carbonate or ground lime. Sweep up and place in suitable container for proper disposal.

SECTION 7 HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING: Wear appropriate personal protective equipment. Ensure adequate ventilation. Avoid contact with skin and eyes.

CONDITIONS FOR SAFE STORAGE: Store in cool, dry, and well-ventilated area. Store away from oxidizing agents.

SECTION 8 EXPOSURE CONTROLS AND PERSONAL PROTECTION

EXPOSURE CONTROLS:

Component	Exposure Limits	Basis	Entity
Nickel (II) Sulfate Hydrate	1 mg/m ³	PEL	OSHA
	0.015 mg/m ³	REL	ACGIH
	0.1 mg/m ³	TLV	OSHA
	10 mg/m ³	IDHL	NIOSH

TLV: Threshold Limit Value over 8 hours of work.

REL: Recommended Exposure Limit

PEL: Permissible Exposure Limit

EYE PROTECTION: Wear chemical safety glasses or goggles and face shield.

SKIN PROTECTION: Wear nitrile or rubber gloves, and a complete suit protecting against chemicals.

VENTILATION: Provide local exhaust, preferably mechanical.

RESPIRATOR: Use an approved respirator.

ADDITIONAL PROTECTION: Provide eyewash stations, quick-drench showers and washing facilities accessible to areas of use and handling.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

COLOR AND FORM: Green solid

ODOR: None

MOLECULAR WEIGHT: 154.76 (anhy.)

BOILING POINT: No data available

MELTING POINT: No data available

SPECIFIC GRAVITY: 2.07 gm/ml

VAPOR DENSITY: No data available

SOLUBILITY: Soluble

SECTION 10 STABILITY AND REACTIVITY

STABILITY: Stable.

HAZARDOUS POLYMERIZATION: Will not occur

CONDITIONS TO AVOID: Reacts with strong oxidizing agents

INCOMPATIBILITY: Oxidizing agents

DECOMPOSITION PRODUCTS: Sulfur oxides and nickel oxides

SECTION 11 TOXICOLOGICAL DATA

ACUTE TOXICITY: LD50 Oral – rat – 500.1 mg/kg. LC50 Inhalation - 4 h - 1.5 mg/l - dust/mist

CARCINOGENIC EFFECTS: Carcinogen to humans

MUTAGENIC EFFECTS: Not available

TETRATOGENIC EFFECTS: Not available

CHRONIC TOXICITY: Not available

RTECS: QR9600000

To the best of our knowledge the toxicological effects of this compound have not been fully investigated.

SECTION 12 ECOLOGICAL DATA

No information available

SECTION 13 DISPOSAL CONSIDERATIONS

Dispose of in according to local, state, and federal regulations.

SECTION 14 TRANSPORTATION DATA

UN3288

Toxic solid, inorganic, n.o.s.

(Nickel (II) Sulfate Hexahydrate)

Class 6.1

PG III

Marine Pollutant: No

SECTION 15 REGULATORY INFORMATION

TSCA: Listed

SARA 302/304: Not Listed

SARA 311/312: Acute Health Hazard, Chronic Health Hazard

SARA (TITLE 313): Nickel (II) Sulfate Hydrate - This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, (title 313) Part 372.

CALIFORNIA PROP. 65: Nickel (II) Sulfate Hydrate – Warning: This product can expose you to chemicals which are known to the State of California to cause cancer.

MASSACHUSETTS RIGHT TO KNOW COMPONENTS: Nickel (II) Sulfate Hydrate

NEW JERSEY RIGHT TO KNOW COMPONENTS: Nickel (II) Sulfate Hydrate

PENNSYLVANIA RIGHT TO KNOW COMPONENTS: Nickel (II) Sulfate Hydrate

SECTION 16 OTHER INFORMATION

DISCLAIMER: The information herein is believed to be accurate and reliable as of the date compiled. However, Prochem, Inc. makes no representation, warranty, or guarantee of any kind with respect to the information in this document or any use of the product based on the information.

DATE PREVIOUSLY PREPARED: 03/15

DATE REVISED: 09/26

REVISION SUMMARY: Removed fax number. Updated the following section numbers; #2, #8, #11, #15 & #16. All other details within this document about this product remained unchanged.

EHS/SDS DEPT.